



Case Study

Jinko ESS's BESS Application for Peak Shaving and Frequency Regulation

2MW/8MWh Li-ion BESS Project in Japan

Project Overview

This case study describes a Japan-specific utility-scale Battery Energy Storage System (BESS) adopting an AC-coupled architecture which connected to grid system.

This project located in Toyohashi-city, Japan, and connected to Japan 6.6kV distribution grid with the following characteristics:

- Strict grid codes and utility specific acceptance criteria

(JEAC 9701, utility test guidelines)

- Mandatory grid connection and commissioning tests, including load break and voltage transient tests.
- It is applicable not only to Japan's energy market for peak shaving, but also to the frequency regulation market (such as primary frequency regulation).

The AC-coupled configuration was selected to enable

independent operation of PV and BESS, provide high system redundancy, and ensure flexibility in meeting evolving grid requirements.




Fig. 1 System Diagram of 2MW/8MWh AC-coupled Project

The Solution

System Architecture

The project applied a conventional AC-coupled configuration as follows:

- An existing FIT system which configuration with PV panels connected to the grid through a dedicated PV-PCS.
- New BESS system connected to the same AC bus via a dedicated BESS-PCS.
- AC power from PV step-up transformer and BESS step-up transformer, integrated to cubicle then connected to POI (Point of interface) of grid.
- Centralized EMS can coordinate PV and BESS operation.

Key Equipment

- 7.52MWh Lithium-ion battery (LFP) system sized for 4-hour rated charge/discharge power.

- 2.75MW dedicated BESS-PCS with four-quadrant operation. (limited to 1990KW output)
- 2300kVA step-up transformer which can convert PCS 690Vac output to 6600Vac.
- Using the cubicle which adopted in Japan, the whole system can be disconnected from grid once emergency or abnormal.
- EMS/SCADA system Connected to all devices required for power plant through Modbus-TCP, and made the whole system run optimally and coordinately.

Grid Compliance Measures

- Configurable power factor control (fixed PF, $\cos\phi(P)$)
- Q-V droop control aligned with utility requirements
- Rate limits on active and reactive power (dP/dt , dQ/dt)
- Coordination logic between PV-PCS and BESS-PCS

Operation Logic

The EMS is responsible for ensuring compliance with both energy market operation and grid frequency supporting.

Energy Market Operation

- During charging periods, PV panels exported AC power to the AC bus and absorbed by the BESS via the BESS-PCS, at the meanwhile insufficient energy can be charged from grid until BESS fully charged.
- During discharge periods, the BESS supplies scheduled active power to the grid, of course PV panels also can generate before sun set.
- PV and BESS operate independently by EMS control, PCS can also prevent reverse power or overload at the POI.

Grid Frequency Supporting

- BESS maintains a controlled SOC range and P-rate to ensure long-duration availability.
- With the EMS monitoring function, BESS-PCS remains synchronized with the grid, capable of immediate P/Q response.
- Reactive power support is continuously available even when active power output is zero.
- Reactive power response is coordinated to prevent over-voltage.
- EMS prioritizes BESS-PCS for voltage control while curtailing PV output if necessary.
- EMS monitoring grid frequency timely, and BESS-PCS can respond to primary frequency regulation ms level with EMS command.




Fig. 2 Jinko ESS Energy Storage Active Power Diagram

Critical grid code results

Grid Connection and Commissioning Tests

- Load Break Test
 - With local EMS coordination logic, transient voltage didn't change significantly due to the prevention of aggressive Q injection.
 - Test results showed voltage maintained within acceptable limits.
- Voltage and Frequency Performance
 - Stable voltage regulation observed under varying grid strength conditions
 - No unintended tripping during frequency or voltage excursions.

Customer Benefits

High Compatibility with Existing PV Plant

- Ideal for projects which PV panels were already installed.
- Minimum modification required for PV plant devices.

Enhanced Redundancy and Reliability

- Separate PCS units reduce single points of failure.
- PV and BESS can operate independently during faults or maintenance.

- Clear separation of responsibilities between PV and BESS systems.

Operational and Business Flexibility

- EMS-based coordination enables participation in multiple services and markets.
- Flexible response to future grid code updates or market changes.
- Can participate in the primary frequency regulation market stably in Japan and achieve higher returns.



Fig. 3 EMS Operation UI Image

* The report serves as a general overview and is subject to updates by Jinko ESS. Jinko ESS reserves the right to modify the content and holds the final authority in its interpretation.



Jinko Solar Co.,Ltd.

No.1, Lane 1466, Shenchang Road,Minhang
District, Shanghai, China
Tel +86 400 860 8878

Case Study

Jinko ESS's BESS Application for Peak Shaving and Frequency Regulation